Sadiq Interlinings

INTERLINING SOLUTIONS SINCE 1999

Thermal Bonded Non-Woven Fusible Interlinings

Double dot interlining range for garment and textile manufacturers - available from 25 to 120 total GSM in white, black and gray.

PRODUCT FAMILY	Thermal bonded double dot non-woven fusible interlining
COMPOSITION	Polyester + low-melt fibre
COATING SYSTEM	PES + PA double dot coating
TOTAL RANGE	25, 30, 40, 50, 70, 80, 100, 110 and 120 GSM
STANDARD WIDTHS	40, 60 and 80 inches
COLOURS	White, black and gray

Selecting the Right Article

Select the total GSM according to the face fabric, garment component and required hand feel. The base and coating weights are stated separately so buyers can compare articles accurately.

Before bulk production, test the actual shell fabric to confirm bond strength, appearance, strike-back, shrinkage and wash-care performance.

Certified Manufacturing Support

Sadiq Interlinings supplies local and export garment manufacturers from Gujranwala, Pakistan. Production and quality systems are supported by ISO 9001 and OEKO-TEX certification.

Samples and technical matching are available against the buyer's fabric, required width, colour, article and order quantity.

For samples or a technical match, share the face fabric, garment application, target hand feel, width, colour, quantity and expected care method.

Sadiq Interlinings

INTERLINING SOLUTIONS SINCE 1999

Technical Product Range

Article-level specifications reproduced from the current Sadiq Interlinings product sheet.

Sr.	Article	Composition	Width	Base GSM	Coating GSM	Total GSM	Coating	Colour
1	DD 7025	Polyester + Lowmelt	40" / 60" / 80"	17	8	25	PES + PA	White / Black / Gray
2	DD 7030	Polyester + Lowmelt	40" / 60" / 80"	22	8	30	PES + PA	White / Black / Gray
3	DD 8040	Polyester + Lowmelt	40" / 60" / 80"	31	9	40	PES + PA	White / Black / Gray
4	DD 8050	Polyester + Lowmelt	40" / 60" / 80"	40	10	50	PES + PA	White / Black / Gray
5	DD 8070	Polyester + Lowmelt	40" / 60" / 80"	59	11	70	PES + PA	White / Black / Gray
6	DD 8080	Polyester + Lowmelt	40" / 60" / 80"	67	13	80	PES + PA	White / Black / Gray
7	DD 100	Polyester + Lowmelt	40" / 60" / 80"	84	16	100	PES + PA	White / Black / Gray
8	DD 110	Polyester + Lowmelt	40" / 60" / 80"	93	17	110	PES + PA	White / Black / Gray
9	DD 120	Polyester + Lowmelt	40" / 60" / 80"	101	19	120	PES + PA	White / Black / Gray

Important	GSM values are nominal product specifications. Final tolerances, availability and order requirements should be confirmed with Sadiq Interlinings.
Production trial	Fusing temperature, pressure and dwell time depend on the outer fabric and machinery. Approve the actual fabric/interlining combination before bulk cutting.